



**ATS ELECTRO-LUBE**  
INTERNATIONAL INCORPORATED

# JACK LUBER™

## Automatic Lubricator with Replaceable Cartridge

The **JACK LUBER** is the most versatile product in the ATS product line. It's built on the proven **ULTIMATE LUBER™** technology incorporating the JACKSCREW mechanism. Together, you know it's powerful! The **JACK LUBER** has a replaceable, one-time use cartridge that changes out in seconds! The drive unit for the **JACK LUBER** is pure **ULTIMATE** power and runs off an ATS battery pack or with a direct AC/DC adaptor (**optional**). The **JACK LUBER** has a maximum continuous operating pressure of 200 psi and is capable of heavy duty applications running long lines; up to 10' through progressive distribution blocks. The **JACK LUBER** is tough, reliable and easy to work with. The **JACK LUBER** saves time, money and gives you the performance you need and trust from ATS!



**JACK 125  
& CARTRIDGE**

**JACK 250  
& CARTRIDGE**

## Features

- Self-contained, stand-alone automatic, single point lubricator.
  - Available in 2 sizes - 125cc & 250cc.
  - Maximum continuous operating pressure up to 200 psi.
  - 1/2" NPT male grease output.
  - Suitable for indoor/outdoor use.
  - Multiple settings to empty from 15 days to 2 years.
  - Custom programming available.
  - May be remote mounted to 30' (9m.) using 3/8" ID hose.
  - **Optional** remote control available to connect to customer equipment or machinery.
  - Replaceable, one-time use cartridge filled with customer specified lubricant. Includes a 2 cell lithium battery pack.
  - Designed for the industrial workplace
    - dust proof
    - weatherproof
- Temperature Range:**  
-40°F to + 140°F (-40°C to + 60°C)  
(NOTE: Low temp lubricants must be used in low temperature applications)  
\*Patent Pending

### Size:

Includes weathercap (not shown)

#### Jack Luber Model 125

7-1/4" H X 3-5/8" D  
18.4 cm H X 9.2 cm D

#### Jack Luber Model 250

9" H X 3-5/8" D  
22.9 cm H X 9.2 cm D



Class I, Div 2, Groups A, B, C, D; Class II, Div 2, Groups F & G; Class III hazardous locations  
T-Code T6 55°C  
250cc pending



In Conformity to European Norms  
Ex nL IIC T3 II 3 G



MADE IN CANADA

[www.atselectrolube.com](http://www.atselectrolube.com)

BUS: (604) 946-1308 FAX: (604) 946-0427 TOLL FREE PHONE: 1-800-663-8141 TOLL FREE FAX: 1-800-663-8140  
7388 Wilson Avenue, Delta, British Columbia, Canada V4G 1H3